

un-du Sticker, Tape & Label Remover

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
SDS ID: AUNDUXX-UND100
Issue date: 6/8/2015 Revision date: 6/7/2021 Supersedes: 6/8/2015 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : un-du Sticker, Tape & Label Remover
Product code : AUNDUXX-004-004

1.2. Recommended use and restrictions on use

No additional information available

1.3. Supplier

Un-du Inc
7600 West 27th Street
Suite B9
St Louis Park, MN 55426 - USA
T 952-929-9300

1.4. Emergency telephone number

Emergency number : Chemtrec - 800-424-9300

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flam. Liq. 2	H225	Highly flammable liquid and vapour
Skin Irrit. 2	H315	Causes skin irritation
STOT SE 3	H336	May cause drowsiness or dizziness
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways

Full text of hazard classes and H-statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

H225 - Highly flammable liquid and vapour
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H336 - May cause drowsiness or dizziness

Precautionary statements (GHS US) :

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground/Bond container and receiving equipment.
P241 - Use explosion-proof electrical/ventilating/lighting equipment.
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P261 - Avoid breathing mist, spray.

un-du Sticker, Tape & Label Remover

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P264 - Wash clothing, hands, forearms and face thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear eye protection, face protection, protective clothing, protective gloves.
P301+P310 - If swallowed: Immediately call a doctor, a POISON CENTER.
P302+P352 - If on skin: Wash with plenty of water.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P312 - Call a doctor, a POISON CENTER if you feel unwell.
P321 - Specific treatment (see a doctor, a POISON CENTER on this label).
P331 - Do NOT induce vomiting.
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P362 - Take off contaminated clothing and wash before reuse.
P370+P378 - In case of fire: Use carbon dioxide (CO₂), dry chemical, foam to extinguish.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Common Name (Synonyms)	Product identifier	%	GHS US classification
Naphtha (Petroleum), Hydrotreated Light	naphtha (petroleum), hydrotreated light	CAS-No.: 64742-49-0	100	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Muta. 1B, H340 Carc. 1B, H350 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

un-du Sticker, Tape & Label Remover

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention. Specific treatment (see supplemental first aid instruction on this label).
First-aid measures after eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/effects after inhalation	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: Highly flammable liquid and vapour.
Explosion hazard	: May form flammable/explosive vapor-air mixture.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.
------------------	---

6.1.1. For non-emergency personnel

Emergency procedures	: Evacuate unnecessary personnel.
----------------------	-----------------------------------

6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection. Avoid breathing dust/fume/gas/mist/vapours/spray.
Emergency procedures	: Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.
-------------------------	--

un-du Sticker, Tape & Label Remover

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	: Handle empty containers with care because residual vapors are flammable.
Precautions for safe handling	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No open flames. No smoking. Use only non-sparking tools. Avoid breathing dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area.
Hygiene measures	: Wash hands, forearms and face thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment.
Storage conditions	: Keep only in the original container in a cool, well ventilated place away from : Keep in fireproof place. Keep container tightly closed.
Incompatible products	: Strong bases. Strong acids.
Incompatible materials	: Sources of ignition. Direct sunlight. Heat sources.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

un-du Sticker, Tape & Label Remover

No additional information available

Naphtha (Petroleum), Hydrotreated Light (64742-49-0)

No additional information available

8.2. Appropriate engineering controls

No additional information available

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Wear protective gloves.

Eye protection:

Chemical goggles or safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. Wear respiratory protection.

un-du Sticker, Tape & Label Remover

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Colorless
Odor	: characteristic
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 208 °F
Flash point	: 25 °F
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Highly flammable liquid and vapour.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Specific gravity / density	: 0.68
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 0.49 mm ² /s
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Highly flammable liquid and vapour. May form flammable/explosive vapor-air mixture.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame.

10.5. Incompatible materials

Strong acids. Strong bases.

un-du Sticker, Tape & Label Remover

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Naphtha (Petroleum), Hydrotreated Light (64742-49-0)

LD50 oral rat	> 5840 mg/kg
LD50 dermal rat	> 2920 mg/kg
LC50 inhalation rat (ppm)	> 23.3 ppm

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : May cause drowsiness or dizziness.

Naphtha (Petroleum), Hydrotreated Light (64742-49-0)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

STOT-repeated exposure : Not classified
Aspiration hazard : May be fatal if swallowed and enters airways.
Viscosity, kinematic : 0.49 mm²/s
Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met.
Symptoms/effects after inhalation : May cause drowsiness or dizziness.
Symptoms/effects after skin contact : Causes skin irritation.
Symptoms/effects after ingestion : May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

un-du Sticker, Tape & Label Remover

Persistence and degradability	Not established.
-------------------------------	------------------

12.3. Bioaccumulative potential

un-du Sticker, Tape & Label Remover

Bioaccumulative potential	Not established.
---------------------------	------------------

12.4. Mobility in soil

No additional information available

un-du Sticker, Tape & Label Remover

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
Additional information : Handle empty containers with care because residual vapors are flammable.
Ecology - waste materials : Avoid release to the environment. Hazardous waste due to toxicity.

SECTION 14: Transport information

14.1. UN number

DOT NA No : UN1206

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Heptanes

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : 3
Hazard labels (DOT) : 3



14.4. Packing group

Packing group (DOT) : II

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

DOT

UN-No.(DOT) : UN1206
DOT Special Provisions (49 CFR 172.102) : IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L

un-du Sticker, Tape & Label Remover

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

Naphtha (Petroleum), Hydrotreated Light (64742-49-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

No additional information available

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 06/07/2021

Other information : None.

Full text of H-phrases	
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Asp. Tox. 1	Aspiration hazard Category 1
Carc. 1B	Carcinogenicity Category 1B
Flam. Liq. 2	Flammable liquids Category 2
Muta. 1B	Germ cell mutagenicity Category 1B
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation

un-du Sticker, Tape & Label Remover

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases	
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H350	May cause cancer
H401	Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.